

CORD TOLERANCE

Rubber cord NB 70 Shore	
Size mm	± Tolerance mm
1.78	0.2
2	0.2
2.4	0.25
2.5	0.25
2.62	0.25
3	0.25
3.2	0.35
3.5	0.35
3.53	0.35
4	0.35
4.5	0.4
5	0.4
5.33	0.4
5.5	0.4
5.7	0.4
6	0.4
6.35	0.55
6.5	0.55
6.99	0.55
7	0.55
7.5	0.55
8	0.55
8.4	0.55
8.5	0.55
9	0.55
10	0.55
11	0.65
12	0.65
13	0.65
14	0.65
15	0.65
16	0.65
18	0.85
20	0.85
22	0.85
25	1
30	1

Rubber cord FPM 75 Shore	
Size mm	± Tolerance mm
2	0.2
2.4	0.2
2.5	0.2
2.62	0.25
3	0.25
3.5	0.3
3.53	0.3
4	0.3
4.5	0.3
4.75	0.3
5	0.3
5.33	0.3
5.5	0.3
5.7	0.3
6	0.3
6.35	0.4
6.5	0.4
6.99	0.4
7	0.4
7.5	0.4
8	0.4
8.4	0.4
8.5	0.4
9	0.4
10	0.4
11	0.5
12	0.5
13	0.5
14	0.5
15	0.5
16	0.5
18	1
20	1
22	1
25 1	1
30	1.3

The above data is obtained through our own laboratory testing on slabs and buttons and als D2137